

# Schulthess Washing machine baseLine 7720 and Dryer baseLine 7730



## baseLine 7720

- Load capacity: 7 kg
- Large 4.3" colour display
- Drum vanes for 3D-Washing
- Drum capacity: 60l
- Spin speed: 1500 rpm
- g Factor 605
- Residual moisture 44%
- With drain valve or drain pump
- Language selection button
- profiClean programme button
- 35 profiClean and 24 freely programmable slots
- Door hinge right or left



## baseLine 7730

- Load capacity: 7 kg
- Large 4.3" colour display
- Stainless steel drum
- LED drum lighting
- Condensation system
- Drum capacity: 118l
- Electronically and time-controlled drying programmes
- Residual moisture measurement
- Language selection button
- Door hinge right or left

# Washing machine baseLine

Company or brand name	Schulthess	
Type of appliance	Washing machine	
Type or sales description	baseLine 7720	
Product number		
Model with drain pump (P)	7720.1PU	
Model with drain valve (V)	7720.1UV	
<b>Application features</b>		
Load capacity	max. kg	7
Drum capacity	l	60
Spinning speed	max. rpm	1500
g Factor	g	605
Residual moisture <sup>1)</sup>	%	44
<b>Structural design</b>		
Footed appliance with work surface	•	
Door hinge <sup>3)</sup>	r/l/w	
<b>Dimensions</b>		
Height	cm	85
Width	cm	60
Depth including distance from wall	cm	67
Depth with door open (front loader)	cm	110
Height (adjustable)	cm	1
Weight when empty	kg	90
<b>Equipment</b>		
Detergent tank and drum	chrome-nickel steel	
Loading opening	Ø cm	34 / 180°
Automatic door opening	•	
Connecting cable	m	1.6
Drain:		
– Drain hose with benda, only model (P)	m	1.5
– Model with drain pump (P)	Ø mm	21
– Model with drain valve (V)	Ø mm	50
<b>Electric power and water supply</b>		
Electrical connection	400V 2N~ / 50Hz / 4,6kW / 10A	
Voltage / connected loads / fuse	230V 1N~ / 50Hz / 2,3kW / 10A	
Water connection		
– Pressure hose G ¾" with fine filter	m	1,5
– Can be connected to cold water / hot water		
– Water pressure	bar	1–10
<b>Options</b>		
	– Door hinge left	
	– Hot water connection	
	– Drum lighting	
	– Drain valve or drain pump	
	– RFID-Card-System	
	– Connection for 8 liquid detergents with dosing pump	
	– Machine plinth	
	– Machine plinth with drawer for fluff filter	
<b>Safety and service</b>		
Conforms to the European Machinery Directive	2006/42/EC	
Country of origin	Switzerland	
Guarantee	1 year	
Service by	Schulthess Maschinen AG	
Name and address of supplier	Schulthess Maschinen AG, CH-8633 Wolfhausen/ZH	

#### Explanations:

- Available or yes      • Not available or no
- 1) Values determined in the 60°C cotton programme.
- 3) In the case of an exhaust air connection at the rear, a greater distance from the wall may be required. Dimensions are to be found in the dimensioned drawings.
- 7) Information on switchover options can be found in the installation instructions, where required.

# Dryer baseLine

Company or brand name	Schulthess	
Type of appliance	Condensation dryer with heat-exchanger air	
Type or sales description	baseLine 7730	
Product number	7730.1U	
Load capacity	max. kg	7
<b>Structural form</b>		
Footed appliance with work surface	•	
Standard unit for wash and dry column	•	
Door hinge <sup>3)</sup>	r/l/w	
<b>Dimensions<sup>4)</sup></b>		
Height	cm	85
Width	cm	60
Depth including space from wall	cm	64
Height for built-in installation	cm	85,5
Depth with door open	cm	122
Height adjustable	cm	2
<b>Drying control</b>		
By time selection <sup>5)</sup>	•	
Automatic by electronic moisture detection <sup>6)</sup>	•	
<b>System and equipment</b>		
Drying technology	Air condensation system	
Programme time display	•	
Load quantity display	•	
Automatic door opening	•	
Loading opening	cm	vorne, Ø 36 / 31 / 180°
LED drum lighting	•	
Connecting cable	m	1,5
Outlet hose	m	2 / Ø 22 mm
Condensate drainage in container / Drainage direct	•	
Exhaust line	–	
Maximum drainage height	m	1
Exhaust hose Ø 100 mm	m	–
<b>Power supply</b>		
Electrical connection <sup>7)</sup>		
Voltage	V	400V 2N~ / 230V 1N~
Connected values	kW	2,8 / 2,1
Fuse protection	AT	10 / 10
<b>Safety and service</b>		
Conforms to the European Machinery Directive	2006/42/EC	
Country of origin	Switzerland	
Guarantee	1 year	
Service by	Schulthess Maschinen AG	
Name and address of supplier	Schulthess Maschinen AG, CH-8633 Wolfhausen/ZH	

#### Explanations:

- Available or yes      • Not available or no
- 3) Door hinge: l = left, r = right, w = can be changed  
Example: l/w means that the machine is delivered with the door hinge to the left, but the direction of opening can be changed.
- 4) The stated dimensions are minimum dimensions for the niche where the machine is built in. Further dimensions can be found in the dimension sheets.
- 5) Set the degree of drying according to the laundry items, as shown in the operating instructions.
- 6) Degree of drying is maintained automatically.
- 7) Information on switchover options can be found in the installation instructions, where required.

## Schulthess Maschinen AG

Landstrasse 37, CH-8633 Wolfhausen ZH  
Tel. 0844 880 880, www.schulthess.ch



# SCHULTHESS

Experts in laundry care